



### Main

Range of product	NSX400...630 Easypact CVS400...630
Range	Compact
Product or component type	Vigi add-on
Device application	Wiring
Range compatibility	Easypact - EasyPact CVS circuit breaker Compact - Compact NSX circuit breaker
Poles description	3P
[In] rated current	400 A 630 A
Earth-leakage add-on module name	MB
Earth-leakage protection class	Class A
Residual earth-leakage sensitivity adjustment type	Adjustable 5 settings
[IΔn] residual earth-leakage sensitive adjustment	0.3...30 A
Residual earth-leakage time delay adjustment type	Adjustable 4 settings
[Δt] residual earth-leakage time delay adjustment	0 ms 150 ms 310 ms 60 ms

### Complementary

Network type	AC
Network frequency	50/60 Hz
[Ue] rated operational voltage	200...440 V AC 50/60 Hz conforming to IEC 60947-2
Earth-leakage protection	With
Maximum breaking time	< 800 ms

Overvoltage category	Class II
----------------------	----------

## Environment

Electrical shock protection class	Class II
Standards	IEC 60947-2

## Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 0818 - Schneider Electric declaration of conformity <a href="#">Schneider Electric declaration of conformity</a>
REACH	Reference not containing SVHC above the threshold <a href="#">Reference not containing SVHC above the threshold</a>
Product environmental profile	Available <a href="#">Product environmental</a>

## Contractual warranty

Warranty period	18 months 12 months
-----------------	---------------------