



Main

Range of product	Acti 9 Clario Librio Prodis
Product or component type	OC contact
Device short name	OF
Signal contacts composition	1 C/O
[In] rated current	3 A at 380...415 V AC - 50/60 Hz 6 A at 220...240 V AC - 50/60 Hz 1 A at 130 V DC 1.5 A at 60 V DC 2 A at 48 V DC 6 A at 24 V DC
[Uc] control circuit voltage	24...130 V DC 24...415 V AC 50/60 Hz
9 mm pitches	1

Complementary

Range compatibility	Acti 9 C120 Acti 9 C60H-DC Acti 9 iDPN Acti 9 DPN Vigi Acti 9 RCCB-ID Acti 9 C60PV-DC Acti 9 C40 Acti 9 ID C40 Acti 9 DT40 Acti 9 DT60 Acti 9 IDc Acti 9 C120NA-DC Acti 9 ITG40 Acti 9 SW60-DC Acti 9 C60NA-DC
---------------------	--

Mounting mode	Fixed
Mounting support	DIN rail
Height	85.3 mm
Width	9 mm
Depth	73.5 mm
Product weight	30 g
Colour	White
Connections - terminals	Clamp terminal in bottom 2 cable(s) 1.5 mm² flexible Clamp terminal in bottom 1 cable(s) 0.5...2.5 mm² rigid Clamp terminal in bottom 2 cable(s) 1.5 mm² flexible with ferrule
Wire stripping length	9 mm
Tightening torque	1 N.m

Environment

Standards	EN/IEC 60947-5-1
Product certifications	ASEFA ASTA KEMA LCIE
IP degree of protection	IP20 conforming to EN/IEC 60947-5-1
Pollution degree	3 conforming to EN/IEC 60947-5-1
Tropicalisation	2 conforming to EN/IEC 60947-5-1
Ambient air temperature for operation	-25...50 °C
Ambient air temperature for storage	-40...85 °C

Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 1001 - Schneider Electric declaration of conformity Schneider Electric declaration of conformity
REACH	Reference not containing SVHC above the threshold Reference not containing SVHC above the threshold
Product environmental profile	Available Product environmental
Product end of life instructions	Available End of life manual

Contractual warranty

Warranty period	18 months 12 months
-----------------	---------------------