

**Part Number: 8723**

Audio, Control & Instrument, #22-2pr, PO, Individ. Foil, PVC Jkt, CM



## Product Description

Audio, Control & Instrument Cable, 22 AWG stranded (7x30) tinned copper conductors, polypropylene insulation, twisted pairs, individually Beldfoil® shielded (100% coverage), 24 AWG stranded tinned copper drain wire, PVC jacket.

## Technical Specifications

### Physical Characteristics (Overall)

#### Conductor

AWG	Stranding	Material	No. of Pairs
22	7x30	TC - Tinned Copper	2

Conductor Count:	4
Conductor Size:	22 AWG

#### Insulation

Material	Nominal Wall Thickness
PP - Polypropylene	0.009 in

#### Color Chart

Number	Color
1	Red & Black
2	Green & White

#### Inner Shield Material

Type	Material	Material Trade Name	Coverage [%]	Drainwire Material	Drainwire AWG	Drainwire Construction n x D
Tape	Aluminum Foil-Polyester Tape	Beldfoil® (Z-Fold®-foil side out)	100 %	TC - Tinned Copper	24	7x32 mm

#### Outer Shield Material

Material
Unshielded

#### Outer Jacket Material

Material	Nominal Diameter	Nominal Wall Thickness
PVC - Polyvinyl Chloride	0.16 in	0.02 in

### Electrical Characteristics

#### Conductor DCR

Individual Pair Nominal Shield DCR	Nominal Conductor DCR
15 Ohm/1000ft	14.7 Ohm/1000ft

#### Capacitance

Nom. Capacitance Conductor to Conductor	Nom. Capacitance Conductor to Other Conductor to Shield
33 pF/ft	62 pF/ft

Shielding:	Individually Foiled + No Overall
------------	----------------------------------

#### Inductance

Nominal Inductance
0.17 µH/ft

## Impedance

### Nominal Characteristic Impedance

52 Ohm

## High Frequency (Nominal/Typical)

### Nom. Insertion Loss

10 dB/100m

## Delay

### Nominal Velocity of Propagation (VP) [%]

66 %

## Current

### Max. Recommended Current [A]

Per conductor @ 25°C (10C temperature rise): 2.3 A

## Voltage

### UL Voltage Rating

300V RMS

## Temperature Range

UL Temp Rating:	60°C
Operating Temp Range:	-20°C To +75°C

## Mechanical Characteristics

Bulk Cable Weight:	17 lbs/1000ft
Max Recommended Pulling Tension:	42 lbs
Min Bend Radius/Minor Axis:	1.75 in

## Standards

NEC Articles:	800
NEC/(UL) Specification:	CM
CEC/C(UL) Specification:	CM
CPR Euroclass:	Eca

## Applicable Environmental and Other Programs

EU Directive 2000/53/EC (ELV):	Yes
EU Directive 2003/96/EC (BFR):	Yes
EU Directive 2011/65/EU (ROHS II):	Yes
EU Directive 2012/19/EU (WEEE):	Yes
EU Directive 2015/863/EU:	Yes
EU Directive Compliance:	EU Directive 2003/11/EC (BFR)
EU CE Mark:	Yes
EU RoHS Compliance Date (yyyy-mm-dd):	2004-01-01
CA Prop 65 (CJ for Wire & Cable):	Yes
MII Order #39 (China RoHS):	Yes

## Suitability

Suitability - Indoor:	Yes
Suitability - Outdoor:	No

## Flammability, LSOH, Toxicity Testing

UL Flammability:	UL1685 (UL Loading)
UL Voltage Rating:	300 V RMS

## Plenum/Non-Plenum

Plenum (Y/N):	No
Plenum Number:	82723, 87723, 88723

## Part Number

**Variants**

Item #	Color	Footnote
8723.001000	Chrome	
8723.0030	Chrome	
8723.00U152	Chrome	
8723.00U305	Chrome	
8723.011152	Chrome	
8723.0111524	Chrome	
8723.013048	Chrome	
8723.01305	Chrome	
8723.013050	Chrome	
8723.01610	Chrome	
8723.02500	Chrome	
8723 060100	Chrome	
8723 0601000	Chrome	C
8723 06010000	Chrome	C Y
8723 06010001	Chrome	C
8723 06015000	Chrome	
8723 0601640	Chrome	
8723 0602000	Chrome	C
8723 0603280	Chrome	C
8723 060500	Chrome	
8723 0605000	Chrome	C
8723 0609999	Chrome	C Y
8723 060U1000	Chrome	
8723 060U2000	Chrome	
8723 060U500	Chrome	

Footnote:	C - CRATE REEL PUT-UP.
Footnote:	Y - FINAL PUT-UP LENGTH MAY VAR -10% TO +20% FROM LENGTH SHOWN. MAY CONTAIN 2 PIECES. MINIMUM LENGTH OF ANY ONE PIECE IS 1500'.

© 2018 Belden, Inc  
 All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.