



# Essential LEDtube Batten

## BN010C 1xTLED L1200 P M EN

This product is one bare batten for matching Philips TLED product with elegant design and more safety

### Product data

General Information		Mechanical and Housing	
Light source replaceable	Yes	Housing Material	Aluminum
Driver/power unit/transformer	Power supply unit	Optic material	-
Driver included	Yes	Optical cover/lens material	-
Optic type	-	Fixation material	Steel
Luminaire light beam spread	-	Optical cover/lens finish	Clear
Connection	Flying leads/wires	Overall length	1222 mm
Cable	Cable without plug 3-pole	Overall width	33 mm
Protection class IEC	Safety class I	Overall height	43.5 mm
CE mark	-	Approval and Application	
Warranty period	1 years	Ingress protection code	IP20 [ Finger-protected]
Constant light output	No	Mech. impact protection code	IK00 [ No protection]
RoHS mark	-	Initial Performance (IEC Compliant)	
Operating and Electrical		Luminous flux tolerance	+/-10%
Input Voltage	220 to 240 V	Init. Color Rendering Index	Not applicable
Input Frequency	50 to 60 Hz	Power consumption tolerance	+/-10%
Controls and Dimming		Application Conditions	
Dimmable	No	Maximum dim level	Not applicable

Essential LEDtube Batten

Suitable for random switching	Not applicable
Product Data	
Full product code	871016330756599
Order product name	BN010C 1xTLED L1200 P M EN
EAN/UPC - Product	8710163307565
Order code	911401576731

Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	20
Material Nr. (12NC)	911401576731
Net Weight (Piece)	0.149 kg



Dimensional drawing

