



### Main

Device application	Distribution
Range	Domae
Product or component type	Miniature circuit-breaker
Poles description	3P
Number of protected poles	3
[In] rated current	16 A
Network type	AC
Curve code	C
Breaking capacity	4500 A conforming to IEC 60898-1 - 400 V AC 50 Hz

### Complementary

Network frequency	50 Hz
[Ue] rated operational voltage	380...415 V AC 50 Hz
Control type	Toggle
Mounting mode	Clip-on
Mounting support	DIN rail
Comb busbar and distribution block compatibility	YES
9 mm pitches	6
Colour	Grey

### Environment

Standards	IEC 60898-1 SNI 04-6507.1
Product certifications	SNI

Disclaimer: Dokumentasi ini tidak ditujukan sebagai pengganti dan tidak digunakan untuk menentukan kesesuaian atau keandalan produk ini untuk aplikasi pengguna

## Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 0627 - Schneider Electric declaration of conformity <a href="#">Schneider Electric declaration of conformity</a>
REACH	Reference not containing SVHC above the threshold <a href="#">Reference not containing SVHC above the threshold</a>
Product environmental profile	Available
Product end of life instructions	Need no specific recycling operations

## Contractual warranty

Warranty period	18 months 12 months
-----------------	---------------------