



### Main

Range	Mini Pragma
Product or component type	Enclosure
Enclosure type	Modular enclosure
Nb of 18 mm modules per row	12
Nb of horizontal rows	2
Type of door	Plain
Width	268 mm outside
Height	353 mm outside
Depth	102 mm outside

### Complementary

Enclosure mounting	Surface
9 mm pitches	24
Total number of 18 mm modules	24
[In] rated current	63 A
Type of rail	35 mm asymmetrical rail
Cable entry	1 bare flange 1 trunking flange
Terminal block function	Earth / neutral
Number of terminal blocks	1 earth terminal block with 16 screwed outgoing 1 neutral terminal block with 16 screwed outgoing
Distribution block outgoing	2 x 16 mm <sup>2</sup> for earth 2 x 16 mm <sup>2</sup> for neutral 6 x 6 mm <sup>2</sup> for earth 6 x 6 mm <sup>2</sup> for neutral 8 x 10 mm <sup>2</sup> for earth 8 x 10 mm <sup>2</sup> for neutral
Enclosure material	Back part : technoplastic Door : technoplastic

Front face : technoplastic

Colour Door : white ( RAL 9003 )  
Front face : white ( RAL 9003 )

## Environment

Standards EN 50102  
IEC 529  
IEC 60439-3  
IEC 60670-24  
IEC 60695-2-11

Quality labels IMQ

Fire resistance Door : 650 °C  
Front face : 650 °C  
Back part : 650 °C

IP degree of protection IP40

IK degree of protection IK07

Ambient air temperature for operation -25...60 °C

## Offer Sustainability

Sustainable offer status Green Premium product

RoHS (date code: YYWW) Compliant - since 0901 - Schneider Electric declaration of conformity

 [Schneider Electric declaration of conformity](#)

REACH Reference not containing SVHC above the threshold

[Reference not containing SVHC above the threshold](#)

Product environmental profile Available

 [Product environmental](#)

Product end of life instructions Need no specific recycling operations

## Contractual warranty

Warranty period 18 months 12 months