



### Main

Range of product	Acti 9 Clario Librio Prodis
Product or component type	Shunt trip release with OC contact
Device short name	MX + OF
Signal contacts composition	1 C/O
[Ie] rated operational current	3 A at 415 V AC 6 A at <= 240 V AC
[Uc] control circuit voltage	100...415 V AC 50/60 Hz 110...130 V DC
9 mm pitches	2
Product compatibility	C40 C60 DT40 IDPN DT60 C120 DPN Vigi ITG40 IDc ID C40

### Complementary

Range compatibility	Acti 9: Acti 9 iDPN Acti 9: Acti 9 DT40 Acti 9: Acti 9 C40 Acti 9: Acti 9 IDc Acti 9: Acti 9 ID C40 Acti 9: Acti 9 ITG40 Acti 9: Acti 9 C120 Acti 9: Acti 9 C60H-DC Acti 9: Acti 9 C60NA-DC Acti 9: Acti 9 C60PV-DC Acti 9: Acti 9 DPN Vigi
---------------------	---

Acti 9: Acti 9 DT60  
Acti 9: Acti 9 ID  
Acti 9: Acti 9 DPN

Local signalling	Action indicator
Mounting mode	Fixed
Mounting support	35 mm symmetrical DIN rail
Height	82.5 mm
Width	18 mm
Depth	73.5 mm
Product weight	65 g
Colour	White
Connections - terminals	Screw clamp terminal bottom 2 cable(s) 1.5 mm <sup>2</sup> flexible Screw clamp terminal bottom 2 cable(s) 1.5 mm <sup>2</sup> flexible with ferrule Screw clamp terminal bottom 1 cable(s) 0.5...2.5 mm <sup>2</sup> rigid
Wire stripping length	9 mm bottom
Tightening torque	1 N.m bottom

## Environment

Standards	EN/IEC 60947-5-1
Product certifications	ASEFA ASTA KEMA LCIE
Tropicalisation	2 conforming to EN/IEC 60947-5-1
Relative humidity	95 % at 55 °C
Ambient air temperature for operation	-25...50 °C
Ambient air temperature for storage	-40...85 °C

## Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 1216 - Schneider Electric declaration of conformity <a href="#">Schneider Electric declaration of conformity</a>
REACH	Reference not containing SVHC above the threshold <a href="#">Reference not containing SVHC above the threshold</a>
Product environmental profile	Available
Product end of life instructions	Need no specific recycling operations

## Contractual warranty

Warranty period	18 months 12 months
-----------------	---------------------