



Main

Range of product	Neo C-Metro
Product or component type	Key card switch
Bulb type	LED blue
Rated current	16 A 250 V AC 50/60 Hz
Colour tint	White

Complementary

Wiring device mounting	Flush Surface
Material	Brass metal parts Polycarbonate plastic part Steel metal parts
Load type	Resistive
Clamping connection capacity	3 x 2.5 mm ² for solid cable(s) 3 x 2.5 mm ² for stranded cable(s) 1 x 4 mm ² for stranded cable(s) 2 x 4 mm ² for stranded cable(s) 1 x 2.5 mm ² for solid cable(s) 1 x 2.5 mm ² for stranded cable(s) 2 x 2.5 mm ² for solid cable(s) 2 x 2.5 mm ² for stranded cable(s)
Connections - terminals	Pillar terminals
Width	87 mm
Height	87 mm
Depth	25 mm

Environment

Ambient air temperature for operation	0...40 °C
Relative humidity	0...95 %
Environmental characteristic	Indoor use

Standards	GB 16915.2 IEC 60669-2-1
-----------	-----------------------------

Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 1809 - Schneider Electric declaration of conformity Schneider Electric declaration of conformity
REACH	Reference not containing SVHC above the threshold Reference not containing SVHC above the threshold
Product environmental profile	Available
Product end of life instructions	Need no specific recycling operations

Contractual warranty

Warranty period	18 months
-----------------	-----------