



Main

Product or component type	Power socket-outlet
Switch function	1-pole
Outlet poles configuration	3P with shutters
Outlet standard	BS 1363 MS 589 SS 145
Colour tint	Grey silver

Complementary

Wiring device mounting	Flush Surface
Rated current	13 A, 250 V, AC, 50/60 Hz
Material	Polycarbonate with grid plate Polycarbonate with surround Brass with contact Copper with silver onlay with bridge Nylon with shutter Steel with brass plating with screws Steel with brass plating with terminals
Load type	Resistive
Connections - terminals	Pillar terminals
Width	147 mm
Height	87 mm
Depth	18 mm

Environment

Ambient air temperature for operation	0...40 °C
Relative humidity	0...95 %
Environmental characteristic	Indoor use

Standards	BS 1363 MS 589 SS 145
-----------	-----------------------------

Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 1809 - Schneider Electric declaration of conformity Schneider Electric declaration of conformity
REACH	Reference not containing SVHC above the threshold Reference not containing SVHC above the threshold
Product environmental profile	Available
Product end of life instructions	Need no specific recycling operations

Contractual warranty

Warranty period	18 months
-----------------	-----------
