



### Main

Range of product	Pieno
Product or component type	Indicator lamp
Local signalling	Please wait neon orange Please clean up neon green Privacy neon red
[Ue] rated operational voltage	250 V AC 50 Hz
Cover frame colour tint	White

### Complementary

Wiring device mounting	Flush Surface
Material	Polycarbonate surround Polycarbonate grid plate
Connections - terminals	By screw
Number of cables	1 2.5 mm <sup>2</sup> solid 1 1.5 mm <sup>2</sup> stranded
Embedding depth	21 mm
Width	87 mm
Height	87 mm
Depth	30.1 mm

### Environment

Ambient air temperature for operation	-5...40 °C
Relative humidity	0...95 %
Standards	BS EN 60669-1 GB 16915.1 IEC 60669-1 MS IEC 60669-1 SS 227-1

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.