



MASTER PL-C 2 Pin

MASTER PL-C 13W/827/2P 1CT/5X10BOX

MASTER PL-C is an efficient medium-wattage compact fluorescent lamp, typically used in general downlights for retail, hospitality and office applications. The original Philips-invented bridge technology guarantees optimum performance in the application, enabling more light and higher efficacy than the bended technology. The 2-pin version is designed for operation on electromagnetic gear and is provided with a plug-in/pull-out lamp base.

Product data

General Information		Operating and Electrical	
Cap-Base	G24D-1 [G24d-1]	Power (Rated) (Nom)	13.4 W
Life to 10% Failures (Nom)	6500 h	Lamp Current (Nom)	0.170 A
Life to 50% Failures (Nom)	10000 h		
LSF 2000 h Rated	99 %	Temperature	
LSF 4000 h Rated	98 %	Design Temperature (Nom)	28 °C
LSF 6000 h Rated	92 %		
LSF 8000 h Rated	78 %	Controls and Dimming	
		Dimmable	No
Light Technical		Mechanical and Housing	
Color Code	827 [CCT of 2700K]	Cap-Base Information	2 Pins
Luminous Flux (Nom)	925 lm		
Luminous Flux (Rated) (Nom)	925 lm	Approval and Application	
Color Designation	Incandescent White	Energy Efficiency Label (EEL)	A
Correlated Color Temperature (Nom)	2700 K	Mercury (Hg) Content (Nom)	1.4 mg
Luminous Efficacy (Rated) (Nom)	69 lm/W	Energy Consumption kWh/1000 h	17 kWh
Color Rendering Index (Nom)	83		
LLMF 2000 h Rated	92 %	Product Data	
LLMF 4000 h Rated	87 %	Full product code	871150062081100
LLMF 6000 h Rated	83 %	Order product name	MASTER PL-C 13W/827/2P 1CT/5X10BOX
LLMF 8000 h Rated	81 %	EAN/UPC - Product	8711500620811

MASTER PL-C 2 Pin


Order code	927904882701
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	50
Material Nr. (12NC)	927904882701

Net Weight (Piece)	53.600 g
ILCOS Code	FSQ-13/27/1B-I-G24d=1

Warnings and Safety

- Use only with electromagnetic control gear
- Lamp light technical and electrical characteristics are influenced by operating conditions, i.e. lamp ambient temperature and operating position
- Dimming is not possible
- A lamp breaking is extremely unlikely to have any impact on your health. If a lamp breaks, ventilate the room for 30 minutes and remove the parts, preferably with gloves. Put them in a sealed plastic bag and take it to your local waste facilities for recycling. Do not use a vacuum cleaner.


Dimensional drawing




Product	D (max)	D1 (max)	A (max)	B (max)	C (max)
MASTER PL-C 13W/827/2P 1CT/5X10BOX	27.1 mm	27.1 mm	97.5 mm	117.0 mm	139.4 mm

PL-C 13W/827/2P

Photometric data





Lightcolor /827




Lightcolor /827

Lifetime



Life Expectancy 3 h cycle



Life Expectancy 12 h cycle

Lumen Maintenance 3h + 12 h cycle

