



Electronic semi-parallel ignitor for HID lamp circuits

SN 58

HID ignitors for semi-parallel systems

Product data

General Information			
Application Code	58		
Operating and Electrical			
Input Voltage	220 to 240 V) V	
Input Frequency	50 to 60 Hz	50 to 60 Hz	
Igniton Type	Semi-Parallel		
Ignition Voltage (Max)	5.0 kV		
Ignition Voltage (Min)	2.8 kV		
Response Voltage	190 V		
Mains Voltage Performance (AC)	-8%-+6%		
Mains Voltage Safety (AC)	-10%-+10%		
Power Losses (Nom)	0.2 W		
Wiring			
Ballast Contact Wire Cross Section	0.50-2.50 mm ²		
Connector Type	Screw		
Temperature			
T-Ambient (Max)	85 °C		


T-Ambient (Min)	-20 °C		
T-Case Maximum (Max)	90 °C		
Mechanical and Housing			
Housing	Akulon S223		
Approval and Application			
Approval Marks	CE marking ENEC certificate		
Product Data			
Full product code	697013372881900		
Order product name	SN 58		
EAN/UPC - Product	6970133728819		
Order code	913710010513		
Numerator - Quantity Per Pack	1		
Numerator - Packs per outer box	48		
Material Nr. (12NC)	913710010513		
Net Weight (Piece)	0.049 kg		

Datasheet, 2018, February 8 data subject to change

Electronic semi-parallel ignitor for HID lamp circuits

Dimensional drawing

SN 58



Product	C1	A1	A2	B1
SN 58	38.5 mm	85.5 mm	65.0 mm	41.5 mm

